

# SKF TWIM 15

A portable solution for bearing heating



A portable solution for bearing heating

## Portable induction heater TWIM 15

The SKF portable induction heater TWIM 15 is designed for applications in maintenance jobs to heat up bearings that are mounted with an interference fit onto a shaft. Heating the bearing causes it to expand, which eliminates the need to use force during installation. Generally, using the TWIM 15 to generate a 90 °C (162 °F) temperature difference between the bearing and shaft is sufficient to enable installation. In addition, the TWIM 15 can be used to heat other ring-shaped, metallic components, providing flexibility of use.



Utilizing electrical power, the TWIM 15 features glass-fiber, high-temperature-resistant plastic construction that allows a low temperature difference between the inner and outer rings of the bearing. This helps to reduce internal tensions that are generated due to excessive thermal expansion of the inner ring compared to the outer ring.

The unit has a user-friendly LED control panel that requires no special training and is simple to understand. The panel is used to regulate temperature and also indicates that the TWIM 15 is operational.

### TWIM 15 advantages:

- Innovative heating of bearings
- Portable, compact and lightweight
- No support yokes required
- Automatic temperature monitoring
- Detects bearing size and heats appropriately
- Different power levels
- User-friendly LED control panel
- Quiet operation



The TWIM 15 portable induction heater package includes:

- Portable induction heater TWIM 15
- Magnetic K-type 400 mm temperature probe TWIM 15-3
- Temperature-resistant gloves TMBA G11
- Instructions for use

**Versatile**

Because of the induction plate's flat shape, a support yoke is not needed. This increases the type of components that can be heated on the plate and also reduces the number of required accessories.

**Portable**

Due to the medium-frequency technology used and choice of materials, the heater is lightweight. Also, the built-in handle makes it convenient to transport, and it can be stored easily.

**Innovative heating**

Utilizing smart construction and operating software, the heater produces a low temperature difference between the inner and outer ring of the bearing. This reduces the internal tensions generated due to excessive thermal expansion of the inner ring compared to the outer ring.



**Power regulation**

Featuring different power settings, the TWIM 15 can heat sensitive components at a slower pace. Also, a non-bearing power configuration is possible where most of the power is focused on the bore of the component.

**Quiet**

Using medium-frequency technology to heat components does not generate noise. An LED indicates when the TWIM 15 is heating, even if you cannot hear it! In parallel, a cooling fan might be heard to help the heater's electronics to stay cool.

Technical data			
Designation	TWIM 15		
Application <sup>1)</sup>		Maximum power	TWIM 15/230 V: 2.3 kVA TWIM 15/110 V: 1.8 kVA
Bearing weight range <sup>2)</sup>	0.5 kg (1.1 lb) - 20 kg (44 lb)	Voltage and frequency	TWIM 15/230 V: 230 V, ±10%, 50/60 Hz TWIM 15/110 V: 110 V, ±10%, 50/60 Hz
Min. bearing bore diameter	30 mm (1.18 in.)	Max. current consumption	TWIM 15/230 V: 10 A TWIM 15/110 V: 16 A
Max. bearing outer diameter	320 mm (12.6 in.)	Temperature control	40-200 °C (104-392 °F)
Max. bearing width	85 mm (3.35 in.)	Demagnetisation	The heater does not magnetise
Performance examples (bearing, weight, temperature, time)	6320: 7.1 kg (15.7 lb), 110 °C (230 °F), 5 min 20 s 22320 CC/W33: 12.8 kg (28.2 lb), 110 °C (230 °F), 12 min 35 s	Dimensions (w x d x h)	450 x 500 x 100 mm (17.7 x 19.7 x 3.9 in.)
		Total weight	6.6 kg (14.6 lb)

<sup>1)</sup> SKF does not recommend heating bearings capped with seals or shields above 80 °C (175 °F). However, if higher temperatures are necessary, please contact SKF.

The heater is designed for maintenance operations where some cooling in between jobs is allowed.

<sup>2)</sup> Depending on the geometry of the bearing, maximum heating temperature and power availability.

Carry your TWIM 15 induction heater in a convenient way

## TWIM 15-BAG

The bag provides extra portability to the TWIM 15 induction heater. It has two pockets to provide space for your heat resistant gloves, the temperature probe and the instructions for use – having the heater and all its accessories together. Like the induction heater, the TWIM 15-BAG has a compact design.

The bag helps you to maintain your heater clean and protected. For example, the bag provides shelter to the heater keeping it free from dust and industrial pollution while stored. The sturdy material of which the bag is made, protects it against scratches from other tools and mishandling. Easy and safe to carry it in the trunk of a car.

It also features a shoulder strap which facilitates bringing the heater into the field. You can carry it now hands free!

### Features:

- Excellent fit for the TWIM 15
- Made of sturdy materials
- Inner pockets for accessory storage
- Shoulder strap for easy carrying
- Compact design

The **SKF TWIM 15-BAG** is optional to the TWIM 15 heater. The heater and bag can also be ordered as a kit, designation: **TWIM 15K**.



Contact Us For More Information.

### **SLS Bearings (S) Pte Ltd**

5 Tuas South Street 15, Singapore 636907

[www.slsbearings.com](http://www.slsbearings.com)

Visit SLS e-shop : [shop.slsbearings.com/sg](http://shop.slsbearings.com/sg)

Phone : (65) 6515 0515

Email : [contact.us@slsbearings.com.sg](mailto:contact.us@slsbearings.com.sg)



[skf.com](http://skf.com) | [mapro.skf.com](http://mapro.skf.com) | [skf.com/lubrication](http://skf.com/lubrication)

© SKF is a registered trademark of the SKF Group.

© SKF Group 2020

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

**PUB MP/P2 18555 EN** · March 2020